



**10 bis 610 kg  
Tragkraft**

## EURO Zylinderkugelrolle

### Gehäuse verzinkt mit Stahlkugel

| Art. Nr.  | Kugel<br>Ø<br>mm | Tragkraft<br>kg | A<br>mm | B<br>mm   | D<br>mm   | F<br>mm | G | H | M<br>mm | L<br>mm | Brutto-Preis<br>exkl. MwSt.<br>CHF |
|-----------|------------------|-----------------|---------|-----------|-----------|---------|---|---|---------|---------|------------------------------------|
| 1.003.500 | 15               | 60              | 31      | 9.5 ±0.2  | 24 ±0.065 | 2.8     | - | - | 6.3     | 21.0    | 7.80                               |
| 1.003.501 | 22               | 160             | 45      | 9.8 ±0.2  | 36 ±0.080 | 2.8     | - | - | 5.5     | 30.0    | 11.40                              |
| 1.003.502 | 30               | 300             | 55      | 13.8 ±0.3 | 45 ±0.080 | 4.0     | - | - | 8.3     | 37.0    | 21.30                              |
| 1.003.503 | 45               | 610             | 75      | 19.0 ±0.4 | 62 ±0.095 | 4.0     | - | - | 10.0    | 53.5    | 56.40                              |

### Gehäuse verzinkt mit Nylonkugel

|           |    |    |    |           |           |     |   |   |     |      |       |
|-----------|----|----|----|-----------|-----------|-----|---|---|-----|------|-------|
| 1.003.507 | 15 | 10 | 31 | 9.5 ±0.2  | 24 ±0.065 | 2.8 | - | - | 6.3 | 21.0 | 10.90 |
| 1.003.508 | 22 | 20 | 45 | 9.8 ±0.2  | 36 ±0.080 | 2.8 | - | - | 5.5 | 30.0 | 16.50 |
| 1.003.509 | 30 | 25 | 55 | 13.8 ±0.3 | 45 ±0.080 | 4.0 | - | - | 8.3 | 37.0 | 38.50 |

### Gehäuse und Kugel Edelstahl-Rostfrei



|           |    |     |    |           |           |     |   |   |      |      |        |
|-----------|----|-----|----|-----------|-----------|-----|---|---|------|------|--------|
| 1.003.504 | 15 | 38  | 31 | 9.5 ±0.2  | 24 ±0.065 | 2.8 | - | - | 6.3  | 21.0 | 21.10  |
| 1.003.505 | 22 | 100 | 45 | 9.8 ±0.2  | 36 ±0.080 | 2.8 | - | - | 5.5  | 30.0 | 27.40  |
| 1.003.506 | 30 | 200 | 55 | 13.8 ±0.3 | 45 ±0.080 | 4.0 | - | - | 8.3  | 37.0 | 54.50  |
| 1.003.499 | 45 | 250 | 75 | 19.0 ±0.4 | 62 ±0.095 | 4.0 | - | - | 10.0 | 53.5 | 159.00 |

Räder, Röllchen, Seil-  
und Gabelrollen

## EURO Schlitzlochkugelrolle Befestigung durch Schrauben oder Popnieten.

### Gehäuse verzinkt mit Stahlkugel

| Art. Nr.  | Kugel<br>Ø<br>mm | Tragkraft<br>kg | A<br>mm | B<br>mm   | D<br>mm   | F<br>mm | G       | H   | M<br>mm | L<br>mm | Brutto-Preis<br>exkl. MwSt.<br>CHF |
|-----------|------------------|-----------------|---------|-----------|-----------|---------|---------|-----|---------|---------|------------------------------------|
| 1.003.549 | 15               | 60              | 31      | 9.5 ±0.2  | 24 ±0.065 | 2.8     | 29 ±0.2 | 3.5 | 6.3     | 21.0    | 8.90                               |
| 1.003.550 | 22               | 160             | 45      | 9.8 ±0.2  | 36 ±0.080 | 2.8     | 42 ±0.2 | 3.5 | 5.5     | 30.0    | 12.10                              |
| 1.003.551 | 30               | 300             | 55      | 13.8 ±0.3 | 45 ±0.080 | 4.0     | 51 ±0.2 | 3.5 | 8.3     | 37.0    | 22.40                              |
| 1.003.552 | 45               | 610             | 75      | 19.0 ±0.4 | 62 ±0.095 | 4.0     | 69 ±0.2 | 4.3 | 10.0    | 53.5    | 57.80                              |

### Gehäuse verzinkt mit Nylonkugel

|           |    |    |    |           |           |     |         |     |     |      |       |
|-----------|----|----|----|-----------|-----------|-----|---------|-----|-----|------|-------|
| 1.003.548 | 15 | 10 | 31 | 9.5 ±0.2  | 24 ±0.065 | 2.8 | 29 ±0.2 | 3.5 | 6.3 | 21.0 | 11.90 |
| 1.003.555 | 22 | 20 | 45 | 9.8 ±0.2  | 36 ±0.080 | 2.8 | 42 ±0.2 | 3.5 | 5.5 | 30.0 | 17.10 |
| 1.003.556 | 30 | 25 | 55 | 13.8 ±0.3 | 45 ±0.080 | 4.0 | 51 ±0.2 | 3.5 | 8.3 | 37.0 | 41.60 |

### Gehäuse und Kugel Edelstahl-Rostfrei



|           |    |     |    |           |           |     |         |     |      |      |        |
|-----------|----|-----|----|-----------|-----------|-----|---------|-----|------|------|--------|
| 1.003.547 | 15 | 38  | 31 | 9.5 ±0.2  | 24 ±0.065 | 2.8 | 29 ±0.2 | 3.5 | 6.3  | 21.0 | 24.30  |
| 1.003.553 | 22 | 100 | 45 | 9.8 ±0.2  | 36 ±0.080 | 2.8 | 42 ±0.2 | 3.5 | 5.5  | 30.0 | 28.90  |
| 1.003.554 | 30 | 200 | 55 | 13.8 ±0.3 | 45 ±0.080 | 4.0 | 51 ±0.2 | 3.5 | 8.3  | 37.0 | 56.70  |
| 1.003.557 | 45 | 250 | 75 | 19.0 ±0.4 | 62 ±0.095 | 4.0 | 69 ±0.2 | 4.3 | 10.0 | 53.5 | 169.00 |

## Empfohlene Nietdurchmesser und Nietabstände

| Kugel-Ø<br>mm | Niet-Ø<br>mm | Nietabstand G<br>mm |
|---------------|--------------|---------------------|
| 15            | 3.2          | 29                  |
| 22            | 3.2          | 42                  |
| 30            | 3.2          | 51                  |
| 45            | 4.0          | 69                  |

**Mengenrabatt auf Anfrage.**

Die Rabattangaben gelten ausschliesslich für das Räder + Rollen-Sortiment.

FTA Fahrzeugtechnik AG  
Dorfbachweg 3  
CH-5035 Unterentfelden  
verkauf@fta.ch

