B9116V

B9125V

B9331V

1820

9500 | 9501 | 9502 | 9503

	Order no.	Capacity kg	Height mm	Blade depth mm	Blade width mm	Total width mm	Solid rubber tyres mm	Net weight kg
ESD-Tubular steel trucks	B9116V	250	1150	300	480	590	260 x 56	18
	B9125V	200	1150	250	320	570	260 x 56	14
	B9331V	300	1300	300	480	580	260 x 56	20

	Order no.	Capacity kg	Wheel-Ø mm	Platform size L x W mm	Outside dimensions L x W x H mm	Shelf heights mm	Net weight kg
ESD-Dolly	1820	250	125	600 x 450	860 x 450 x 875	195, 770	15
ESD-Open carts	9500	500	160	850 x 500	970 x 509 x 950	235	24
	9501	600	200	1000 x 600	1120 x 609 x 990	276	30
	9502	600	200	1000 x 700	1120 x 709 x 990	276	33
	9503	600	200	1200 x 800	1320 x 809 x 990	276	38

ESD-Tubular steel trucks B9116V | B9125V | B9331V

Electric static discharge construction
(ESD = Electrostatic Discharge).

Handy tubular steel trucks with steel sheet blades, sturdy welded construction, conductive powder coating, slate grey, RAL 7015. Safety grips. Steel sheet front shovel mountable, therefore exchangeable. ESD-Solid rubber tyres on synthetic rims, hubs with roller bearings. Bar and transversal struts.

ESD-Dolly with gooseneck handle 1820

made of tubular steel welded, handle bolted on.

Capacity of upper shelf 100 kg.

ESD-Open carts 9500 | 9501 | 9502 | 9503

Electric static discharge construction
(ESD = Electrostatic Discharge).

Tubular steel and sectional steel welded, conductive powder coating, slate grey, RAL 7015. Screw and plug type construction. Shelves made of electrically conductive wood material according to DIN 68765, light grey.

2 swivel and 2 fixed-wheel castors with TPE-ESD tyres (thermoplastic elastomer), electrically conductive. Hubs with precision groove ball bearing. Castors with wheel lock.

Maximum comfort: Very low starting, rolling and swivelling resistance. Low noise operation on level floors. Tyres are non-marking.

Accessories on pages 183-185

Online-Shop: www.fta.ch / Tel. 062 737 04 04