



Storeroom trolleys with steps

Welded tubular and sectional steel, powder coated. Shelves made of derived timber material boards in angle steel frame, 12 mm high skirting.

2 swivel and 2 fixed-wheel castors, TPE tyres. Hubs with groove ball bearing.

Swivel castors with wheel locks.

Capacity upper and middle shelves 80 kg.

At the face ends wooden steps lifting automatically when released and standing firmly on the floor when under load, whereby the trolley is automatically locked. You can hold onto or lean against the safety handle provided. The steps can be tilted easily assisted by a gas spring.

Utility model

20 2014 009 975.8

2105 | 2106

When steps are fold out the total length increases by 185 mm.

2107 | 2108

When steps are fold out the total length increases by 430 mm.

Accessories

Scanner holder 1392

Steel sheet, powder coated RAL 7035.

With adjustable bolt-on points at the back and sides. Tubular strut with multiple holes, with clamping bracket for attaching the scanner bag onto almost all of our products in virtually any position.

Scanner intake W x D x H:

120 x 87 x 150 mm

Front opening: 40 mm wide

Accessories

on pages 183-185



2105



2106



2107



2108



Steps tilted



Bottle holder

For details see page 185.



Tablet holder

For details see page 87.



Scanner holder

Virtually any position.



Order no.	Capacity kg	Wheel-Ø mm	Platform size L x W mm	Outside dimensions L x W x H mm	No. of shelves	Height of step mm	Clearance betw. steps	Shelf heights mm	Net weight kg
2105	250	125	1000 x 600	1322 x 611 x 1155	2	504	252	200, 820	45
2106	250	125	1000 x 600	1322 x 611 x 1155	3	504	252	200, 510, 820	57
2107	250	125	1000 x 600	1322 x 611 x 1880	3	928	232	200, 825, 1445	64
2108	250	125	1000 x 600	1322 x 611 x 1880	4	928	232	200, 680, 1155, 1630	77
1392	—	—	—	—	—	—	—	—	1