



4586



4596



4588



4562



Roller conveyor



Extended platform



Steps tilted

## Tyre trolleys

Tubular steel and steel section construction, powder coated blue RAL 5007.

### 4586

Tyre carrier variable adjustable in intervals of 150 mm with clamps on the face ends.

For tyre diameter 250 - 750 mm.

4 swivel castors, TPE tyres, hubs with groove ball bearing. Swivel castors with wheel lock.

### 4596

Shelves with welded wire lattice 140 x 40 mm.

Carriers variably insertable within a distance of 120 mm. Due to the joint-like attachment, the carriers adapt automatically to the tyre size.

For tyre diameter 380 - 750 mm.

2 swivel and 2 fixed-wheel castors, TPE tyres, hubs with groove ball bearing. Swivel castors with wheel locks.

### 4588

As 4586, but reinforced version for heavy duty, e.g. for motor-sports as tyre trolley in pit lane.

For tyre diameter 400 - 780 mm.

4 swivel castors with blue-grey elastic tyres, hubs with ball bearing. 2 wheels with locks.

### 4562

For comfortable order picking of wheels and tyres. Tyre carrier with robust roller conveyors with fall through protection for easy moving of loaded wheels and tyres with 550 - 850 mm Ø.

Upper shelf screwable in height of 1.253 or 1.153 mm, capacity 80 kg.

At face ends 4 wooden steps lifting automatically when released and locking the trolley via rubber feet when under load. Safety stand on upper step by extended platform.

Safety handle to hold onto or lean against. The steps can be completely tilted assisted by a gas spring.

4 swivel castors, TPE tyres, hubs with groove ball bearing. Swivel castors with wheel lock.

	Order no.	Capacity kg	Wheel-Ø mm	Platform size L x W mm	Outside dimensions L x W x H mm	Net weight kg
Tyre trolleys	4586	250	160	1420 x 600	1540 x 670 x 1725	40
	4596	400	200	1420 x 610	1600 x 620 x 1800	62
	4588	500	200	1860 x 618	1991 x 671 x 1671	62
Tyre trolleys	4562	250	125	1000 x 588	1343 x 625 x 1749	63

Accessories on page 184-185